

## 2.3.6 Closed-Circuit Rebreather Diver Level 2

### 2.3.6.1 Course Outcomes

GUE's Closed-Circuit Rebreather Diver Level 2 course is designed to educate individuals in advanced rebreather technologies and to cultivate diver proficiency in the use of GUE-approved rebreather configurations. The course is also designed to enhance deep diving proficiency while using hypoxic helium diluent and bailout gases and oxygen-enriched decompression gases.

Other course outcomes include: the use of multiple bailout stages; use of hypoxic gas mixtures and required hypoxic protocols; gas management; oxygen management; extended decompression; accelerated, omitted, and general decompression strategies; dive planning; and management of multiple cylinders.

### 2.3.6.2 Prerequisites

Applicants for a CCR 2 course must:

- a. Submit a completed Course Registration Form, Medical History Form, and Liability Release Form to GUE HQ.
- b. Hold insurance that will cover diving emergencies such as hyperbaric treatment, e.g., DAN Master-level insurance or equivalent.
- c. Be physically and mentally fit.
- d. Be a nonsmoker.
- e. Obtain a physician's prior written authorization for the use of prescription drugs, except for birth control, or for any medical condition that may pose a risk while diving.
- f. Be a minimum of 21 years of age.
- g. Be a certified GUE Closed-Circuit Rebreather Diver Level 1 diver.
- h. Have completed at least 50 non-training closed-circuit rebreather dives beyond GUE Closed-Circuit Rebreather Diver Level 1 certification.
- i. Have completed at least 25 non-training closed-circuit rebreather dives beyond GUE Closed-Circuit Rebreather Level 1 certification, deeper than 100 ft/30 m.
- j. Own a GUE-approved closed-circuit rebreather.

### 2.3.6.3 Course Content

The Closed-Circuit Rebreather Diver Level 2 course is normally conducted over six days. It requires a minimum of eight dives and at least forty-eight hours of instruction, encompassing classroom lectures, land drills, and at least ten hours of in-water work.

### 2.3.6.4 Closed-Circuit Rebreather Diver Level 2 Specific Training Standards

- a. Student-to-instructor ratio is not to exceed 6:1 during land drill or surface exercises; it cannot exceed 3:1 during any in-water training.
- b. Maximum depth of 250 ft/75 m
- c. Dives must not be planned to incur more than 60 minutes of unadjusted decompression time, as established by GUE's DecoPlanner.
- d. No overhead diving
- e. The oxygen supply valve must never be closed completely during drills.

### 2.3.6.5 Required Training Materials

GUE training materials and recommended reading as determined by the course study packet received via online download after GUE course registration.

### 2.3.6.6 Academic Topics

- a. Introduction: GUE organization and course overview (objectives, limits, expectations)
- b. Human factors
- c. Rebreather operation and procedures
- d. Failure management
- e. Strategies necessary for a successful dive, decompression planning, absorbent management, gas and gas reserve management
- f. Continuance management

### 2.3.6.7 Land Drills and Topics

- a. Basic rebreather operation review
- b. Basic rebreather failure management review
- c. Basic open-circuit failure management review
- d. Bailout and out-of-gas procedures review
- e. Gas switching review
- f. Advanced rebreather operation
- g. Advanced rebreather failures
- h. Bailout, including the use of a bottom stage and ascent with two additional gas switches and a tank rotation
- i. Off-board use of oxygen and diluent
- j. Semi-closed rebreather operation

### 2.3.6.8 Required Dive Skills and Drills

- a. Demonstrate a safe and responsible demeanor throughout all training.
- b. Demonstrate proficiency in underwater communication.
- c. Demonstrate proficiency in managing a closed-circuit rebreather configuration.
- d. Demonstrate proficiency with the use of the rebreather during ascents, descents, and diving.
- e. Demonstrate good buoyancy and trim, i.e., approximate reference is a maximum of 20 degrees off horizontal while remaining within 3 ft/1 m of a target depth.
- f. Must be able to swim at least 500 yds/450 m in less than 14 minutes without stopping. This test should be conducted in a swimsuit and, where necessary, appropriate thermal protection.
- g. Must be able to swim a distance of at least 60 ft/18 m on a breath hold while submerged.
- h. Demonstrate ability to manage gas failures, including valve manipulation, out-of-gas scenarios, and regulator switching as appropriate.
- i. Demonstrate the ability to manage a flooded closed-circuit rebreather while discharging excess water.
- j. Demonstrate the ability to diagnose and correctly respond to simulated rebreather problems.
- k. Demonstrate the ability to switch and maintain desired  $pO_2$  setpoints manually throughout a dive.

- l. Demonstrate effective ability to connect and use off-board O<sub>2</sub> or diluent gas.
- m. Demonstrate effective ability to dive the rebreather in semi-closed mode.
- n. Demonstrate proficiency in removing, rotating, and re-attaching stage cylinders while hovering horizontally.
- o. Demonstrate the ability to comfortably switch gases while maintaining good trim and neutral buoyancy.
- p. Demonstrate proficiency in safe diving procedures, including assembly and setup; rebreather pre-dive checklist; rebreather on-site checklist; CHAOS critical control checks and 5-minute pre-breathe; GUE-EDGE; flow check; in-water activity; and post-dive assessment, breakdown, and maintenance.
- q. Efficiently and comfortably demonstrate how to donate gas to an out-of-gas diver while using the rebreather.
- r. Be able to comfortably demonstrate use, manipulation, and failure management of the gas addition systems supplying the rebreather.
- s. Demonstrate awareness of a team member's closed-circuit rebreather function and an overall concern for safety, responding quickly to visual or audible indications and dive partner needs during diving and failures.

#### 2.3.6.9 Equipment Requirements

GUE base equipment configuration as outlined in Appendix A, plus:

- a. Modified tank configuration as appropriate for use with a GUE-approved closed-circuit rebreather
- b. Modified regulator configuration as appropriate for use with a GUE-approved closed-circuit rebreather
- c. A GUE-approved closed-circuit rebreather
  - i. The student must own their own GUE-approved closed-circuit rebreather before attending the course; they can, however, use a rented or borrowed unit during the course.
  - ii. The closed-circuit rebreather used by the student, with all associated components, must be fully functional (pass all tests on the rebreather pre-dive checklist) and serviced according to manufacturer specifications.
  - iii. All oxygen sensors must be less than one year from manufacturing date.
  - iv. Both the rebreather controller and SOLO board must be updated with the latest software and firmware versions published by the manufacturer.
- d. Spare parts and consumables, including one set of controller, HUD, and solenoid batteries; one oxygen sensor; and one DSV/BOV mouthpiece
- e. One primary and two backup lights
- f. Three stage cylinders with stage regulators
  - i. Two decompression stages
  - ii. One bottom stage
  - iii. All stage regulators must have a low pressure inflator hose, allowing them to be connected to the rebreather manual addition valve (MAV).
- g. One stage leash with a double-ender
- h. One primary reel per team

- i. Drysuit inflation system independent from back gas cylinders (while breathing a helium mixture, if using a drysuit). If using a drysuit inflation cylinder attached to the backplate, extended inflation cylinder straps need to be used to ensure that it does not interfere with or restrict the counterlung's function.

Prior to the commencement of the class, students should consult with a GUE representative to verify equipment requirements and appropriateness of any selected equipment.

## Appendix A - GUE Base Equipment Configuration

The GUE base equipment configuration is comprised of:

- a. Tanks/cylinders: Students may use a single tank/cylinder with a single- or dual-outlet valve. Students may also use dual tanks/cylinders connected with a dual-outlet isolator manifold, which allows for the use of two first stages. Dual tanks/cylinders connected with a dual-outlet, non-isolator manifold can be used, but only in recreational (no decompression) diving, and are considered an alternative for a single tank/cylinder. Consult course-specific standards and your instructor to verify size requirements.
- b. Regulators:
  - i. Single tank: The first stage must supply a primary second stage via a 5 to 7 ft/1.5 to 2 m hose. A backup second stage must be necklaced and supplied via a short hose. The first stage must also supply an analog pressure gauge, inflation for the buoyancy compensator (BC), and (when applicable) inflation for a drysuit.
  - ii. Double tank: One first stage must supply a primary second stage via a 5 to 7 ft/1.5 to 2 m hose (7 ft/2 m hose is required for all cave classes), and inflation for the buoyancy compensator (BC). The other first stage must supply a necklaced backup second stage via a short hose, an analog pressure gauge, and (when applicable) inflation for a drysuit.
- c. Backplate system:
  - i. Is held to the diver by one continuous piece of webbing. This webbing is adjustable and uses a buckle to secure the system at the waist.
  - ii. A crotch strap is attached and looped through the waistband to prevent the system from riding up a diver's back.
  - iii. The continuous webbing must support five D-rings;
    1. The first placed at the left hip
    2. The second placed in line with a diver's right collarbone
    3. The third placed in line with the diver's left collarbone
    4. The fourth and fifth are placed on the front and back of the crotch strap when divers plan to use advanced equipment such as DPVs.
  - iv. The harness below the diver's arms has small restrictive bands to allow for the placement of backup lights. The webbing and system retains a minimalist approach.
- d. Buoyancy compensation device (BC):
  - i. A diver's BC is back-mounted and minimalist in nature.
  - ii. It is free of extraneous strings, tabs, or other material.
  - iii. There are no restrictive bands or restrictive elastic affixed to the buoyancy cell.

- iv. Wing size and shape is appropriate to the cylinder size(s) employed for training.
- e. At least one time/depth measuring device
- f. Wrist-mounted compass
- g. Mask and fins: Mask is low-volume; fins are rigid, non-split.
- h. Backup mask
- i. At least one cutting device
- j. Wetnotes with pencils
- k. Surface marker buoy (SMB) with spool: when required, the SMB should be appropriate for environmental conditions and deployed using a spool with at least 100 ft/30 m of line.
- l. Exposure suit appropriate for the duration of exposure

### **Additional Course-Specific Equipment**

- a. Where required, back gas and stage cylinders are marked in accordance with the GUE General Training Standards, Policies, and Procedures document and configured in line with GUE protocols.
- b. When drysuit inflation systems are applicable, they should be sized appropriately for the environment; small tanks are placed on the left side of the backplate with larger supplies affixed to the diver's left back gas tank.
- c. Underwater lights:
  - i. When required, backup lights should be powered by alkaline batteries (not rechargeable) and stowed on the D-rings at a diver's chest.
  - ii. Backup lights should have a minimal amount of protrusions and a single attachment at the rear.
  - iii. The primary light should consist of a rechargeable battery pack and be fitted with a Goodman-style light handle.
  - iv. When burn time requirements create the need for an external battery pack, it should reside in a canister mounted on the diver's right hip.
- d. Guideline devices, as required during cave diving activities:
  - i. A primary reel is required for all cave diving and provides a minimalist form factor with a handle designed to support a Goodman or "hands free" handle operation. The primary reel must contain at least 150 ft/45 m of line.
  - ii. A safety spool is required for each diver while cave diving and must contain at least 150 ft/45 m of line.
  - iii. A jump or gap spool is required during Cave 2 diving and must contain at least 75 ft/23 m of line.